



DATA CABINET

Available : 6U - 42U



- Color: Black or Grey
- Front door: Tempered glass;
- Rear door: metal
- Mounting profile: 2.0mm ;
- Horizontal Beam: 1.2mm
- Front/rear/top/frame: 1.2mm ;
- Side Panel: 1.0mm



- Color: Black or Grey
- Front Door : Tempered glass ;
- Rear Door: Metal
- Reliable 19" international structure, single section
- Removable side panels with plastic fasteners for easy operation, lock is for options

ATX CASING

G1603



Include
700W Povesupply

- M/B FF : ITX, Micro ATX, ATX
Materials: 0.4mm SPCC; ABS Front Panel
Exp. Slot : 7 Drive Bays: 3.5 x 2; 2.5 x 1
Front I/O : Power Button; Reset Button; USB1.0 x 2; Mic; HD Audio
Fan Size : 120mm F: 3 R: 1

CHALLENGER



Include
700W Povesupply

- M/B FF : Micro ATX, ATX
Materials: 0.4mm SPCC; ABS Front Panel
Exp. Slot : 7
Drive Bays: Ext. 5.25 x 1; 3.5 x 1
Int. 3.5 hdd x 2; 2.5 x 1
Front I/O : Power Button; Reset Button; USB1.0 x 2; Mic; HD Audio
Fan Size : 120mm F: 2 R: 1 S: 1

SLIM CASING

Q5



Include
600W Povesupply

- M/B Form Factor: Micro ATX, ATX
Materials : 0.5mm SECC; Steel Side Panel
Expansion Slot : 4 Drive Bays:
3.5 hdd x 1; 2.5 x 1; DVD Bays
Front I/O : Power Button;
USB2.0 x 2; Mic; HD Audio

MICRO ATX CASING

M109



Include
700W Povesupply

- M/B FF : Micro ATX, ITX
Materials: 0.4mm SPCC; Black interior
ABS Front Panel
Exp. Slot : 4
Drive Bays: 3.5 x 2; 2.5 x 1
Front I/O : Power Button; Reset Button;
3 USB (2 x 2.0); HD Audio
Fan Size : 120mm F: 2 R: 1

M173-3BB



Include
700W Povesupply

- M/B FF : Micro ATX, ATX
Materials: 0.4mm SPCC; ABS Front
Metal Side Panel
Exp. Slot : 4
Drive Bays: Ext. 5.25 x 1; 3.5 x 1
Int. 3.5 x 2; 2.5 x 1
Front I/O : Power Button; Reset Button;
3 USB (2 x 2.0); HD Audio
Fan Size : 120mm F: 2 S: 1 R: 1 (80mm)

V200



M/B FF : Micro ATX, ITX
Materials: 0.4mm SPCC; ABS Front
Metal Side Panel

- Exp. Slot : 4
Drive Bays: 3.5 x 2; 2.5 x 2
Front I/O : Power Button; Reset Button;
(2 x USB2.0); HD Audio
Fan Size : 80mm R: 1

V200



M/B FF : Micro ATX, ITX
Materials: 0.4mm SPCC; ABS Front
Metal Side Panel

- Exp. Slot : 4
Drive Bays: 3.5 x 2; 2.5 x 2
Front I/O : Power Button; Reset Button;
(2 x USB2.0); HD Audio
Fan Size : 80mm R: 1

POWERSUPPLY

P800

ATX Powersupply



- FAN: 12cm
- SATA: 2
- 20+4pin: Yes
- HDD/Molex: 2
- 4pin for CPU: Yes
- 4 pin for Floppy: 1

P700

ATX Powersupply



- FAN: 12cm
- SATA: 2
- 20+4pin: Yes
- HDD/Molex: 2
- 4pin for CPU: Yes
- 4 pin for Floppy: 1

PM-600

Micro ATX Powersupply



- FAN: 12cm
- SATA: 2
- 20+4pin: Yes
- HDD/Molex: 2
- 4pin for CPU: Yes
- 4 pin for Floppy: 1

WEBCAM

812H



- 1/2.9 2MP
- 0.5-2.5meters
- 3.6mm.
- MJPG,h.264, YUV2
- 1020x1080
- 30 FPS
- Built-in Microphone
- 2.5meters
- PCM
- 33kbp
- USB direct power

RACKMOUNT CASING

DVR-4U

ATX PSU



Support E-ATX 12" X13" Motherboard
Drive Configuration:
8X3.5" HDD + 2X5.25" CD-ROM
Fan: 4X8025 fans in the front
**Case Only*

UTP CABLE

CAT 6 Outdoor



- 305m
- 24AWG .45 CCA* Pairs
- Copper Clad Aluminum
- Black

CAT 6



- 305m and 100m available
- 24AWG .45 CCA* Pairs
- Copper Clad Aluminum
- Blue

CAT 5e



- 305m and 100m available
- 24AWG .45 CCA* Pairs
- Copper Clad Aluminum
- White

CCTV POWERSUPPLY

DVR-2U

ATX PSU



Support E-ATX 12" X13" Motherboard
Drive Configuration:
8X3.5" HDD + 2X5.25" CD-ROM
Fan: 4X8025 fans in the front
**Case Only*

18CH 12V 30A



- Switching power supply module,
- The output terminal with multiple sets of terminals
- Easy field installation and commissioning
- Up to 30ch; DC12V 30A
- (1 year warranty)

18CH 12V 20A



- without back-up battery option
- with back-up battery option
- Switching power supply module,
- The output terminal with multiple sets of terminals
- Easy field installation and commissioning
- Up to 18ch; DC12V 20A
- (1 year warranty)

9CH 12V 10A



- without back-up battery option
- with back-up battery option
- Switching power supply module,
- The output terminal with multiple sets of terminals
- Easy field installation and commissioning
- Up to 9ch; DC12V 10A
- (1 year warranty)

AUTOMATIC VOLTAGE REGULATOR

AVR-1200F



- Power - 1200W
- Input Voltage - 160-260V
- Output Voltage - 220Vac
- Frequency - 60Hz
- Delay Time - 6 secs/ 3mins.
(other brand 3secs./3mins.)

AVR-1000F



- Power - 1000W
- Input Voltage - 160-260V
- Output Voltage - 220Vac
- Frequency - 60Hz
- Delay Time - 6 secs/ 3mins.
(other brand 3secs./3mins.)

AVR-300



- Power - 300W
- Input Voltage - 180-260V
- Output Voltage - 220Vac
- Delay Time - 6 secs/ 3mins.
(other brand 3secs./3mins.)

Philippine Distributor:

PHITEQ
ENTERPRISE INC.

Authorized Reseller: