

uFace402 TIME AND ATTENDANCE 4.3" Touch Screen Face Cap. : 3,000 Fingerprint : 4,000 Card Cap. : 10,000	Horus E1-PP TIME AND ATTENDANCE Base On Horus E1 Adding following function: FP : 6,000 RFID : 10,000 ID standard Communication: TCP/IP, RS485 Optional: Access control module DM10	uFace800/ID/ADMS/Battery TIME AND ATTENDANCE Face cap. : 3,000 Fingerprint : 4,000 Palm : 3,000 Card Cap. : 10,000 Record Cap.: 100,000	IClock880/ID/ADMS TIME AND ATTENDANCE Face cap. : 3,000 Fingerprint : 4,000 Palm : 3,000 Card Cap. : 10,000 Record Cap.: 100,000	
Multibio800/ID/ADMS TIME ATTENDANCE 2.8 inch TFT LCD Color Face Cap. : 400 Fingerprint Cap. : 1,000 Transaction Cap.: 100,000	MB560VL +ID +WIFI TIME AND ATTENDANCE 2.8" TFT Screen Face Cap. : 3,000 Fingerprint : 3,000 Card Cap. : 10,000 Transactions: 100,000 Memory : 256M RAM/ 8G ROM	TF1700 TIME AND ATTENDANCE 1.54" OLED Screen Face Cap. : 3000 Card Cap. : 50,000 Record Cap. : 1,000,000	SilkFP-101TA/ID TIME AND ATTENDANCE 2.8" TFT Screen Fingerprint : 3,000 Card Cap. : 10,000 Record Cap.: 100,000	
VF380/ID TIME AND ATTENDANCE 2.8" Touch Screen Face Cap. : 3,000 Card Cap. : 50,000 Record Cap. : 1,000,000	UA300 TIME AND ATTENDANCE 2.8-inch TFT Screen Fingerprint : 3,000 Card Cap. : 10,000 Record Cap. : 100,000	UA400 TIME AND ATTENDANCE 2.8" Screen Fingerprint : 3,000 Card Cap. : 10,000 Record Cap.: 100,000	X6328-C TIME ATTENDANCE 3.0" TFT Screen Fingerprint : 3,000 Card Cap. : 10,000 Record Cap.: 100,000	
UA760/ID/ADMS TIME ATTENDANCE 2.8" TFT Screen Fingerprint : 1,000 Card Cap. : 1,000 Record Cap.: 80,000	MB460/ID/ADMS TIME ATTENDANCE 2.8" TFT Screen Face Cap. : 1,500 Fingerprint : 2,000 Card Cap. : 500 Record Cap: 100,000	UA860/ID/ADMS TIME AND ATTENDANCE 2.8" color screen Fingerprint : 3,000 User Cap. : 5,000 Record Cap.: 50,000	EFACE10 +ID +WIFI TIME AND ATTENDANCE 4.3" Touch Screen Face Cap. : 500 Fingerprint : 3,000 Card Cap. : 1,000 Transactions: 150,000 Memory : 256M RAM /512Flash OS : Linux	D2 TIME ATTENDANCE Fingerprint : 1000 Record Cap.: 50,000
K40 - ID TIME AND ATTENDANCE 2.8" TFT Screen Fingerprint : 1,000 Card Cap. : 1,000 Record Cap.: 80,000	K30/ID TIME ATTENDANCE 2.8" TFT Screen Fingerprint : 3,000 ID Card Cap. : 3,000 Record Cap. : 100,000	MB10-VL/ID/ADMS TIME AND ATTENDANCE 2.8-inch TFT Screen Face Cap. : 100 Fingerprint : 500 Card Cap. : 500 Transactions: 50,000 Memory : 256M RAM/256Flash OS : Linux	K14 - ID TIME AND ATTENDANCE 2.8" TFT Screen Fingerprint : 3,000 Card Cap. : 500 Record Cap. : 100,000	LX50 TIME AND ATTENDANCE Fingerprint : 50,000 Card Cap. : 50,000 Record Cap.: 800,000 IP65
G4/ID TIME ATTENDANCE 7" Touch Screen Face Cap. : 10,000 Fingerprint : 10,000 MF Card Cap. : 10,000 Record Cap. : 1,000,000	G3/ID TIME ATTENDANCE 3.5" TFT Color Screen Fingerprint : 20,000 ID Card Cap. : 20,000 Record Cap. : 200,000	G2/ID TIME ATTENDANCE 3.5" TFT Color Screen Face Cap. : 3,000 Fingerprint : 5,000 ID Card Cap. : 10,000 Record Cap. : 100,000	G1/ID TIME ATTENDANCE 2.8" TFT Color Screen Fingerprint : 5000 ID Card Cap. : 15,000 Record Cap. : 100,000	S922 PORTABLE TIME AND ATTENDANCE 2.8" TFT Screen Fingerprint : 500 User Cap. : 500 Record Cap. : 50,000

5V Mini Ups TA ACCESSORIES Rechargeable backup battery T.A. biometric with 5V input power.	12V Mini Ups TA ACCESSORIES Rechargeable backup battery T.A. biometric with 12V input power.	12V DC AC ADAPTER TA ACCESSORIES Directly supply 12V 3A AC Adapter to the Fingerprint Device	5V/12V DC ADAPTER TA ACCESSORIES 5V 2A or 12V 1.5A for Fingerprint Device
ProFace-X/TD ACCESS CONTROL Fever Detection Terminal Face Cap. : 30,000 Palm Cao. : 5,000 Card Cap. : 1,000,000 Record Cap: 80,000	ProFace X ACCESS CONTROL 8" iK04 Touch Screen Face Cap. : 30,000 Card Cap. : 50,000 Transactions: 1,000,000	ProRT-T/ID ACCESS CONTROL 2.4" TF Colored Touch Card Cap. : 50,000 Transactions: 100,000 User Photos : 3,000 Event Photo : 7,000	SpeedFace-V5L/TD ACCESS CONTROL Temperature Detection Terminal Face Cap. : 6,000 Palm Cap. : 5,000 Fingerprint: 6,000 Transaction : 200,000 Memory : 512M RAM / 8G ROM
SpeedFace V5L+Mifare+WIFI ACCESS CONTROL 5"LCD Color Touch Screen Face Cap. : 6,000 Fingerprint : 6,000 Palm Cap. : 3,000 Card Cap. : 10,000 Transaction : 200,000 Memory : 512M RAM / 8G ROM	SpeedFace V5L +ID +WIFI ACCESS CONTROL 5" Colored Touch Screen Face Cap. : 6,000 Fingerprint : 6,000 Palm Cap. : 3,000 Card Cap. : 10,000 Transactions: 200,000 Memory : 256MB RAM 512MB FLASH	SpeedFace V5L/QR + WIFI ACCESS CONTROL 5" Colored Touch Screen Face Cap. : 6,000 Palm Cap. : 3,000 Card Cap. : 10,000 Transactions : 200,000 Memory : 1G RAM 8G ROM	SpeedFace V4L + WIFI ACCESS CONTROL 4" Colored Touch Screen Face Cap. : 1,000 Palm Cap. : 1,000 Card Cap. : 1,000 Transactions : 150,000 Memory : 512MB RAM 512MB FLASH
SpeedFace V3L + WIFI ACCESS CONTROL 2.4" Colored Touch Screen Face Cap. : 500 Palm Cap. : 3,000 RFID Cap. : 3,000 Transactions: 200,000 Memory : 256MB RAM 512MB FLASH	SpeedFace V3L + QR + WIFI ACCESS CONTROL 2.4" Colored Touch Screen Face Cap. : 500 Card Cap. : 3,000 Transactions: 200,000 Memory : 256MB RAM 512MB FLASH	SpeedFace V3L Light + WIFI ACCESS CONTROL 2.4" Colored Touch Screen Face Cap. : 500 RFID : 500 Transactions: 200,000 Memory : 256M RAM 8G ROM	SpeedFace-H5L ACCESS CONTROL 5" LCD Color Touch Screen Face Cap. : 6,000 Fingerprint : 6,000 Card Cap. : 10,000 Transaction : 200,000 Memory : 512M RAM 8G ROM
F22/Mifare/ADMS ACCESS CONTROL 2.4" TFT LCD Color Screen Fingerprint : 3,000 Card Cap. : 5,000 Record Cap.: 30,000	F22/ID/ADMS (ZLM60) ACCESS CONTROL 2.4" TFT LCD Color Screen Fingerprint : 3,000 Card Cap. : 5,000 Record Cap.: 30,000	F7-C ACCESS CONTROL 2" Color Display Fingerprint : 2,200 Card Cap. : 5,000 Record Cap.: 100,000	SF400 + ID ACCESS CONTROL 2.8" Colored Touch Screen Fingerprint: 1,500 Card Cap. : 5,000 Log Cap. : 80,000
SF400 E LOCK KIT ACCESS CONTROL 1 x SF400 1 x AL-100 (Dropbolt Lock) 1 x PS901B 1 x TLEB102-R 10pcs. Prox Cards 10pcs. Prox. Tags	SF400 EM LOCK KIT ACCESS CONTROL 1 x SF400 1 x AL-280 (Magnetic Lock) 1 x PS901B 1 x TLEB102-R 10pcs. Prox. Cards 10pcs. Prox. Tags	Card box ACCESS CONTROL • Cardbox Including • Cardbox Spant • Card Reader (KR101E) • Box (install on device) • BOM version: A34090093_V1.5	INBIO460 PRO BOX CONTROLLER PACKAGE Packaged Contents: 1 x Inbio460 Pro Controller - Firmware: Push SDK - Users: 30,000 - Records: 100,000 - Communication: TCP/IP - Software: ZKBioSecurity 1 x Metallic Box 1 x Power Supply
INBIO260 PRO BOX CONTROLLER PACKAGE Packaged Contents: 1 x Inbio260 Pro Controller - Firmware: Push SDK - Users: 30,000 - Records: 100,000 - Communication: TCP/IP - Software: ZKBioSecurity 1 x Metallic Box (Black) 1 x Power Supply	INBIO160 PRO BOX CONTROLLER PACKAGE Packaged Contents: 1 x Inbio160 Pro Controller - Firmware: Push SDK - Users: 30,000 - Records: 100,000 - Communication: TCP/IP - Software: ZKBioSecurity 1 x Metallic Box (Black) 1 x Power Supply	INBIO460 PACKAGE B MULTI DOOR ACCESS CONTROL Packaged Contents: 1 x Inbio460 Controller - Users: 30,000 - Records: 100,000 - Software: ZKaccess 3.5 (FREE) 1 x Metallic Box 1 x Power Supply	INBIO260 PACKAGE B MULTI DOOR ACCESS CONTROL Packaged Contents: 1 x Inbio260 Controller - Users: 30,000 - Records: 100,000 - Software: ZKaccess 3.5 (FREE) 1 x Metallic Box 1 x Power Supply

INBIO160 PACKAGE B MULTI DOOR ACCESS CONTROL Packaged Contents: 1 x Inbio160 Controller - Users: 30,000 - Records: 100,000 - Software: ZKAccess 3.5 (FREE) 1 x Metallic Box 1 x Power Supply	INBIO160 POE BUNDLE PACKAGE B MULTI DOOR ACCESS CONTROL Packaged Contents: 1 x Inbio160 POE Controller - Users: 30,000 - Records: 100,000 - Software: ZKAccess 3.5 (FREE) 1 x Metallic Box 1 x Power Supply	INBIO460 PRO PACKAGE B MULTI DOOR ACCESS CONTROL 4 Doors 8 Ways Biometric Access Control Panel Firmware : Push SDK CPU: 32bit 400MHz CPU RAM : 32M Flash Memory:128M bits User : 60,000 Fingerprint : 20,000 Event Buffer: 100,000	INBIO460 PRO PACKAGE B MULTI DOOR ACCESS CONTROL 4 Doors 8 Ways Biometric Access Control Panel Firmware : Push SDK CPU: 32bit 400MHz CPU RAM : 32M Flash Memory:128M bits User : 60,000 Fingerprint : 20,000 Event Buffer: 100,000	DF01 Card AC ACCESSORIES • UHF Dual Frequency • Frequency: 125KHz & UHF • Printed 10 digit decimal card • Wiegand 34 output • ProtocolID: ISO/EM4001 • UHF:ISO/IEC 18000-6C	DF02 Card AC ACCESSORIES • UHF Dual Frequency • Frequency: 13.56KHz & UHF • Printed 10 digit decimal card • Wiegand 34 output • ProtocolID: ISO/14443A • UHF:ISO/IEC 18000-6C	S70 (Thin card) AC ACCESSORIES • 13.56Mhz • Mifare One Card • Standard MFI S70 (4 Kbyte) EEPROM	S50 (Thin card) AC ACCESSORIES • 13.56Mhz • Mifare One Card • Standard MFI S50 (1 Kbyte) EEPROM	ID Thick card AC ACCESSORIES • 125kHz Proximity Card • Read only
INBIO460 PRO MULTI DOOR ACCESS CONTROL 4 Doors 8 Ways Biometric Access Control Panel Firmware : Push SDK CPU: 32bit 400MHz CPU RAM : 32M Flash Memory:128M bits User : 60,000 Fingerprint : 20,000 Event Buffer: 100,000	INBIO260 PRO MULTI DOOR ACCESS CONTROL 2 Doors 4 Ways Biometric Access Control Panel Firmware : Push SDK CPU: 32bit 400MHz CPU RAM : 32M Flash Memory:128M bits User : 60,000 Fingerprint : 20,000 Event Buffer: 100,000	FR1200 MULTI DOOR ACCESS CONTROL • Read Fingerprint • Proximity card • Communication: • RS485 with inBIO controller or Fingerprint devices • DIP switch for RS485 address	PROID101 MULTI DOOR ACCESS CONTROL • IP65, IK04 • Wiegand(26/34) & RS485 • 125k ID card • Mini Mount size • Dimension: 111*44.5*11mm. • Optional: 13.56MHz IC card , • Color: White (MOQ 50 pcs)	AL-280 (LED) AC ACCESSORIES Power-on to lock • Holding Force : 210kg±10kg • Working Voltage : DC12V/24V input	AL-280 (LED) AC ACCESSORIES Power-on to lock • Holding Force : 2*270kg • Working Voltage : DC12V/24V input	AL-280PL AC ACCESSORIES L bracket for AL 280(LED) To install the lock body	AL-280PZ AC ACCESSORIES Z bracket for AL-280(LED) To install the iron plate	AL-280PU AC ACCESSORIES U bracket for AL 280/280D To install the iron plate on the glass door
TLEB101-R AC ACCESSORIES • Non touch Exit Sensor • Remote Key (Diffused Detection) • NO NC COM relay • Size: 86L*86W(mm) • With Blue/Red Light • Include one free RM-100	TLEB102-R AC ACCESSORIES • Non touch Exit Sensor • Remote Key (Diffused Detection) • NO NC COM relay • Size: 86L*86W(mm) • With Blue/Red Light • Include one free RM-100	RM-100 AC ACCESSORIES Remote Key for TLEB101-R and TLEB102-R	EX-801A AC ACCESSORIES • Metal Exit Button • 91L x 28W x 20T mm	AL-280DPL AC ACCESSORIES L-bracket for AL 280D(LED) To install the lock body	AL-100PF AC ACCESSORIES Power-on to lock Working Voltage : DC12V/24V input Holding Force : 150kg	AL-180 AC ACCESSORIES Power-on to lock Working Voltage : DC12V/24V input Holding Force : 150kg	AL-180D AC ACCESSORIES Power-on to lock Working Voltage : DC12V/24V input Holding Force : 2*150kg	AL-180M AC ACCESSORIES Power-on to lock Holding Force : 150kg Working Voltage : DC12V/24V input
EX-806B AC ACCESSORIES • Metal Exit Button with Key • NO/NC/COM with key	P1205-B2 AC ACCESSORIES AC Input Voltage Range : AC220~AC240V Working Current : DC12V 2A Instantaneous Current : DC12V 5A Overload Protection DC12V 5A Over Voltage Protection: 115%~135% Withstand Voltage : I/P-O/P:3kVAC	TPM003B AC ACCESSORIES • For InBIO160 Package B • AC Adapter for Controller • W/ uninterrupted battery • Input:110-240V AC, 50/60Hz • Output: 13.8V/3A+1A	TPM005B AC ACCESSORIES • For InBIO260/460 Package B • AC Adapter for Controller • W/ uninterrupted battery • Input:110-240V AC, 50/60Hz • Output: 13.8V/3A+1A	AL-180PL AC ACCESSORIES Power-on to lock Holding Force : 150kg Working Voltage : DC12V/24V input	AL-180DPL AC ACCESSORIES L-bracket for AL-180D To install the lock body	AL-180PZ AC ACCESSORIES Z-bracket for AL-180/180D To install the iron plate	AL-180PU AC ACCESSORIES U-bracket for AL-180/180D To install the iron plate on the glass door	AL-200PZ AC ACCESSORIES U-bracket for AL-180/180D To install the iron plate on the glass door
KR602E/M SLAVE READER • Wiegand 26bit/34bit • 6-14V DC • 70mA • 125khz • <300ms reading time • 0-10cm	KR600E SLAVE READER • Wiegand 26bit • 6-14V DC • 70mA • 125khz • <300ms reading time • 0-10cm	KR600M SLAVE READER • Wiegand 34bit • 6-14V DC • 70mA • 13.56Mhz • <300ms reading time • 0-5cm	KR702E SLAVE READER • Wiegand 26bit • 12V DC • <90mA • 125khz • 80ms reading time • 0-8cm distance	AL-500D(LED) AC ACCESSORIES Power-on to lock Holding Force : 2 * 500 kg Working Voltage : DC12V/24V input	AL-500DPL AC ACCESSORIES L-bracket for AL-500D(LED) To install the lock body	AL-500(LED) AC ACCESSORIES Power-on to lock Holding Force: 460kg±10kg Working Voltage: DC12V/24V input	AL-500 PL AC ACCESSORIES L bracket for AL-500(LED)/500D(LED) To install the lock body	AL-500 PZ AC ACCESSORIES L bracket for AL-500(LED)/500D(LED) To install the lock body
FR-1500MF SLAVE READER • RS485 Fingerprint Reader, • Single gang. • Standard: ID card. • Optional: Mifare, HID, iclass card.	FR-1500ID SLAVE READER • RS485 Fingerprint Reader, • Single gang. • Standard: ID card. • Optional: Mifare, HID, iclass card.	FR-1300ID SLAVE READER • RS485 Fingerprint Reader, • Single gang. • Standard: ID card. • Optional: Mifare, HID, iclass card.	CR60W CARD ISSUER USB Reader Read 13.56 MHz proximity card USB interface	AL-500 PU AC ACCESSORIES U bracket for AL-500/500D To install the iron plate on the glass door	LB-12 ELECTRIC BOLT LOCK	LB-22 ELECTRIC BOLT LOCK	LB-35 ELECTRIC BOLT LOCK	UBB-1 ELECTRIC BOLT LOCK
CR20E CARD ISSUER USB Reader Read 125K proximity card USB interface	CR20M CARD ISSUER USB Reader Read 13.56MHz mifare card USB interface	ZK8500R/MF CARD ISSUER • USB interface • Capture fingerprint • Read ID/MF card	SLK20R CARD ISSUER • Desktop USB • Fingerprint acquisition, support Win10/8/7, • support USB only. • Firmware version: V2.30.	ProID10 WE ProID10 BE CARD READER • Read 125KHz Proximity ID card • Wiegand output 26bit	UBB-1 ELECTRIC BOLT LOCK	LBB-1 ELECTRIC BOLT LOCK	LBB-2 ELECTRIC BOLT LOCK	L-300S ACCESSORIES

AS603 OTHER ACCESSORIES  <ul style="list-style-type: none"> Siren 12V DC 	AS31 OTHER ACCESSORIES  Emergency break glass	ZKABK-900A OTHER ACCESSORIES  Emergency door release	ENERGY SAVING SWITCH OTHER ACCESSORIES  Energy saving switch	DS10 OTHER ACCESSORIES  Wi-Fi door sensor with the double reed switch	SBTL8011 Pro (1.2 High barrier) 2 RFID CARD READERS; C3-200 SBTL8022 Pro (1.2 High barrier) RFID+2 FINGERPRINT; CARD READERS INBIO260 SBTL8033 Pro (1.2 High barrier) LEAVE HOLE FOR FACEDEPOT 7B-CH	SBTL8200 ENTRANCE CONTROL  Standard <ul style="list-style-type: none"> 1.2m high barrier Driver control board, AC Adapter 	TS8211 Pro (1.2 High barrier) 2 RFID CARD READERS AND C3-200 TS8222 Pro (1.2 High barrier) RFID+2 FINGERPRINT; CARD READERS; INBIO260 TS8233 Pro (1.2 High barrier) STANDARD; LEAVE HOLE FOR FACEDEPOT 7B-CH	SBTL8200 ENTRANCE CONTROL  Single Lane Swing Barrier Turnstile standard Features	FFC ENTRANCE CONTROL ACCESSORIES  Connector fingerprint sensor and core-board.
TS1000 Pro SMART SECURITY GATE 	Mars-B1000 SMART SECURITY GATE / SINGLE LANE 	Mars-B1200 SMART SECURITY GATE / DUAL LANE 	Mars-F1000 SMART SECURITY GATE / SINGLE LANE 	Mars-F1200 SMART SECURITY GATE / DUAL LANE 	TSA10 OPTIONAL ACCESSORIES Fingerprint reader installation module for TS1000/TS1200 	CMP200 PARKING BARRIER  <ul style="list-style-type: none"> Chassis with LED, 4.5m telescope boom (w/o led) AC Adapter :220V, Boom length: 4.5m (2.5m+2.2m, Adjustable) Open/close :3s Support Change Direction 	CMP200 BOOM : 6MM; AC 220; OPEN/CLOSE : 6 SEC CMP200 BOOM : 4.5MM; AC 110; OPEN/CLOSE : 3 SEC CMP200 BOOM : 6MM; AC 220; OPEN/CLOSE : 6 SEC	CMP200 (YELLOW CHASSIS) PARKING BARRIER  <ul style="list-style-type: none"> Chassis with LED, Telescope boom (w/o led) AC Adapter :220V, Boom length: 4.5m (2.5m+2.2m, Adjustable) Open/close :3s Support Change Direction 	
BLADE6040 XRAY <ul style="list-style-type: none"> Conveyor Speed : 0.20 m/sec. ~0.40m/sec Load on Conveyor: Max 200 kg. Space Definition : Horizontal Ø 1.0mm, Vertical Ø 2.0mm Steel Penetration : 38mm Guaranteed Wire Resolution : 38AWG Guaranteed 	ZKX100100D XRAY <ul style="list-style-type: none"> Double screen console, Dual view screening Bi-directional scanning, Fingerprint login 	ZKX100100 XRAY <ul style="list-style-type: none"> Double screen console, Bi-directional scanning, Fingerprint login Steel Penetration 34 mm Wire Resolution 38 AWG 	ZKX10080D XRAY <ul style="list-style-type: none"> Double screen console Dual view screening Bi-directional scanning Fingerprint login 	CMP200 (YELLOW CHASSIS) PARKING BARRIER  <ul style="list-style-type: none"> Chassis with LED, 4.5m telescope boom (w/o led) AC Adapter :220V, Boom length: 6m (3.2m+3m, Adjustable) Open/close :3s Support Change Direction 	CMP200 (Boom w/ LED) PARKING BARRIER  <ul style="list-style-type: none"> Chassis with LED, 4.5m telescope boom AC Adapter :220V, Boom length: 4.5m (2.5m+2.2m, Adjustable) Open/close :3s Support Change Direction 	CMP200 (Boom w/ LED) BOOM : 6MM; AC 220; OPEN/CLOSE : 6 SEC CMP200 (90° Folding Boom w/o LED) BOOM : 4MM; AC 220; OPEN/CLOSE : 3 SEC CMP200 (90° Folding Boom w/o LED) BOOM : 6MM; AC 220; OPEN/CLOSE : 6 SEC	CMP200-W (wooden box) PARKING BARRIER  <ul style="list-style-type: none"> Chassis with LED, 4.5m telescope boom AC Adapter :220V, Boom length: 4.5m (2.5m+2.2m, Adjustable) Open/close :3s Support Change Direction 		
ZKX10080 XRAY <ul style="list-style-type: none"> Double screen console Bi-directional scanning Fingerprint login Steel Penetration 34 mm Wire Resolution 38 AWG 	ZKX6550D XRAY <ul style="list-style-type: none"> Double screen console, Dual view screening Fingerprint login 	ZKX6550 XRAY <ul style="list-style-type: none"> Single screen console Bi-directional scanning login 21" screen display Steel Penetration 38mm Wire Resolution 40 AWG 	ZKX6550A XRAY <ul style="list-style-type: none"> Pseudo color image Single screen console Bi-directional scanning Fingerprint login 21inch screen display Steel Penetration 10mm Wire Resolution 38 AWG 	CMP200 (Wooden Box) BOOM : 6MM; 220V; OPEN/CLOSE : 6 SEC CMP200 (90° Folding Boom w/o LED) BOOM : 4.5MM; 110V; OPEN/CLOSE : 3 SEC CMP200 (90° Folding Boom w/o LED) BOOM : 6MM; 110V; OPEN/CLOSE : 6 SEC	CMP200-W (Wooden Box) PARKING BARRIER  <ul style="list-style-type: none"> Yellow Chassis with LED, 4.5m telescope boom AC Adapter :220V, Boom length: 4.5m (2.5m+2.2m, Adjustable) Open/close :3s Support Change Direction 	PB4030 - L PB4030 - R PARKING BARRIER  <ul style="list-style-type: none"> Straight Boom Barrier Gate Only 4m boom, 3s opening & closing time 	PB4030 - L PB4030 - R PARKING BARRIER  <ul style="list-style-type: none"> Straight Boom Barrier Gate Only 6m boom, 6s opening & closing time 		
ZKX6040A XRAY <ul style="list-style-type: none"> Input & Output Rollers Bi-directional scanning, Fingerprint login 21.5 inch screen display Steel Penetration 8mm Wire Resolution 34 AWG 	ZKX6040 XRAY <ul style="list-style-type: none"> Input & Output Rollers Bi-directional scanning Fingerprint login 21" screen display Steel Penetration 35mm Wire Resolution 38 AWG 	ZKX5030C XRAY <ul style="list-style-type: none"> 17" screen display; Steel Penetration 32mm Wire Resolution 38 AWG 	ZKX5030A XRAY <ul style="list-style-type: none"> Pseudo color image 17" screen display Steel Penetration 8mm Wire Resolution 34 AWG 	PB4130 - L PB4130 - R PARKING BARRIER  <ul style="list-style-type: none"> 90° Folding Boom Barrier Only 3m boom, 3s opening & closing time 	PSA26 PARKING BARRIER ACCESSORIES  Infrared Intrusion Detectors (with bracket) one transmitter and one receiver	VR10 PRO PARKING BARRIER ACCESSORIES  Detection Distance : 1m to 6m Working Frequency : 79GHz Working Voltage : DC 10V to 16V Working Current : 0.2A Power Consumption : ≤2.5W Transmitter Power Output: 12.5dBm Antenna Gain : 10dBi Interface : Bluetooth, RS485, Relay	PSA02 (Loop Detector) PARKING BARRIER ACCESSORIES  Working voltage : AC 230/110V Rated power : 4.5W Voltage of relay : AC 120V/3A Working temperature: 20°C ~ 65°C Working humidity : 10% ~ 90% Working frequency : 20 kHz ~ 170 kHz Time : Infinite / limited 5 min. Reaction time : 10 ms Recommended inductance of the coil : 80-300 μH		
SBTL5011 SWING BARRIER  <ul style="list-style-type: none"> RFID w/ 2 RFID card readers and 1inBIO260Pro Serial Starts with LSR 	SBTL5211 SWING BARRIER  <ul style="list-style-type: none"> RFID w/ 2 RFID card readers and 1inBIO260Pro Serial Starts with LSR 	TS2000 Pro ENTRANCE CONTROL  Standard Contain : <ul style="list-style-type: none"> Driver Control Board AC Adapter 	TS2011 Pro ENTRANCE CONTROL  RFID Comes with: <ul style="list-style-type: none"> 2 RFID card readers InBIO260Pro Serial Starts with LSR" 	PSA03 (Loop Coil) PARKING BARRIER ACCESSORIES  Loop Coil Number lived : 1 Operating voltage: 300V/500V Cable section : 1sq. mm.	UHF1-Tag2 AC ACCESS CONTROL 	TBM01 TICKET DISPENSER  Entrance Support ID/MF Card	TBM02 TICKET DISPENSER  Exit Code scanning machine Support ID/MF Card		
TS2022 Pro ENTRANCE CONTROL RFID Comes with: <ul style="list-style-type: none"> 2 RFID card readers InBIO260Pro Serial Starts with LSR" 	TS1000 Pro ENTRANCE CONTROL  Standard <ul style="list-style-type: none"> Driver control board, AC Adapter) 	TS1011 Pro 2 RFID CARD READERS ;1 C3-200 TS1022 Pro RFID+P; 2 FR1200; INBIO260 TS1022 Pro 2 FR1200/MIFARE AND 1 INBIO260 PRO	SBTL8000 ENTRANCE CONTROL  Standard <ul style="list-style-type: none"> 1.2m high barrier Driver control board, AC Adapter 	UR20RFW CARD ISSUER READER  <ul style="list-style-type: none"> UHF Tags ,UHF Cards 902MHz-928Mhz 0 to 5cm valid distance USB analog keyboard output DC 5V (±4%) 50 to 300mA 	UHF5 Pro Series UHF RFID READER  <ul style="list-style-type: none"> 2-8 meters range Trigger to Read & Always Read (Default) 7-color LED indicators Support Wiegand and RS485 Protection level of IP66 	UHF10 Pro Series UHF RFID READER  <ul style="list-style-type: none"> 10-20 meters range Trigger to Read & Always Read (Default) 7-color LED indicators Support Wiegand and RS485 Protection level of IP66 	TSA11 AC ACCESSORIES  RFID reader installation module for TS1000/TS1200	KJZ-03 AC ACCESSORIES  Aluminum Alloy 80*38*370mm For FaceDepot-7A/ FaceDepot-7B/ SpeedFace-V5 FaceDepot-7BL/ SpeedFaceV5L/ProFace X FaceDepot-7BL(TDI)/ SpeedFace-V5L(TD)	

C3-400 Package B C3 CONTROLLER Packaged Contents: • 1 x C3-400 Controller - Users: 30,000 - Records: 100,000 - Software: ZKaccess 3.5 (FREE) • 1 x Metallic Box	C3-200 Package B C3 CONTROLLER Packaged Contents: • 1 x C3-200 Controller - Users: 30,000 - Records: 100,000 - Software: ZKaccess 3.5 (FREE) • 1 x Metallic Box • 1 x Power Supply	C3-100 POE Bundle C3 CONTROLLER Packaged Contents: • 1 x C3-100 POE Controller - Users: 30,000 - Records: 100,000 - Software: ZKaccess 3.5 (FREE) • 1 x Metallic Box	C3-100 Package B C3 CONTROLLER Packaged Contents: • 1 x C3-100 Controller - Users: 30,000 - Records: 100,000 - Software: ZKaccess 3.5 (FREE) • 1 x Metallic Box • 1 x Power Supply	SENTRY SOFTWARE Cloud-based Access and Time Management System. Simplified time tracking to save time and be more productive	SoftwareNet3.0 (BASIC) SOFTWARE Client/Server(PC based) 50 Devices; 500 Employees	SoftwareNet3.0 (ECONO) SOFTWARE Client/Server(PC based) 50 Devices; 1000 Employees	SoftwareNet3.0 (PREMIUM) SOFTWARE Client/Server(PC based) 50 Devices; 2000 Employees	ZKBT-Dev-PR10 (BASIC) BIOTIME 8.0 SOFTWARE Maximum Device Qty : 10 ; Maximum User : 500		
EX16 Package B ELEVATOR CONTROL GREEN LABEL • 2 pieces EX16, • AC Adapter • Metal box	EX16 Package A ELEVATOR CONTROL GREEN LABEL • 1 piece EX16, • AC Adapter • Metal box	EC10 Package B ELEVATOR CONTROL GREEN LABEL • 1 piece EC10, • AC Adapter • Metal box		ZKBT-Dev-P20 (ECONOMIC) BIOTIME 8.0 SOFTWARE Maximum Device Qty : 20 ; Maximum User : 1,000	ZKBT-Dev-P50 (PREMIUM) BIOTIME 8.0 SOFTWARE Maximum Device Qty : 50 ; Maximum User : 2,000	ZKBT-Dev-P100 (PROJECT) BIOTIME 8.0 SOFTWARE Maximum Device Qty : 100 ; Maximum User : 5,000	ZKBT-Dev-P200 (PROJECT) BIOTIME 8.0 SOFTWARE Maximum Device Qty : 200 ; Maximum User : 10,000	ZKBT-Dev-P500 (PROJECT) BIOTIME 8.0 SOFTWARE Maximum Device Qty : 500 ; Maximum User : 25,000		
ZK-D4330 METAL DETECTOR 7" LCD display Zones : 33 zones Input Voltage : DC15V LED indicators : 4 LED light bars Sensitivity Level: 500 Networking(TCP/IP):standard Wooden frame packing: Standard Touch Panel : Standard	ZK-D3180S (TD) METAL DETECTOR WITH TEMPERATURE MEASUREMENT 7" LCD display Working Frequency : 4kHz ~ 8kHz Temp. Sensor Type : IR temp. sensor Temp. Meas. Time : ≤1s Temp. Meas. Point : Forehead or wrist Temp. Meas. Distance: 50mm ~ 100mm Temp. Sensor from the Ground: 150(mm) Temp. Meas. Deviation: ±0.5°C (±0.9°F) Temp. Range : 30°C ~ 45°C Interval Bet.Temp. Meas.: 2s	ZK-D3180 METAL DETECTOR 7" LCD display Zone : 18 Frequency : 5.7KHz ~ 9.6KHz Voltage : DC12V Working Current : 1.2A Running Power : 14W TCP/IP comm./APP Linkage with turnstile	ZKBT-Dev-P10 BIOTIME 8.0 SOFTWARE Maximum Device Qty : 1,000 ; Maximum User : 50,000	ZKBT-Dev-UM (ULTIMATE) BIOTIME 8.0 SOFTWARE More than 1,000 devices	ZKBT-AoD-20 BIOTIME 8.0 SOFTWARE Add-on Devices: 20	ZKBT-AoD-50 BIOTIME 8.0 SOFTWARE Add-on Devices: 50	ZKBT-AoD-100 BIOTIME 8.0 SOFTWARE Add-on Devices: 100			
ZK-D300 METAL DETECTOR Power voltage : Standard 9V bat. Operating voltage: 7V-9V Operating Current : <50mA Alarm terms : Sound (vibration) and light alarm simultaneously Waterproof : IP31 Alarm Sound : ≥75dB(A) Op. Frequency : 40KHz	ZK-D100S METAL DETECTOR Power voltage : Standard 9V bat. Operating voltage: 7V-9V Operating Current : <50mA Alarm terms : Sound (vibration) and light alarm simultaneously Waterproof : IP31 Alarm Sound : ≥75dB(A) Op. Frequency : 40KHz	ZK-D100S METAL DETECTOR Power voltage : Standard 9V bat. Operating voltage: 7V-9V Operating Current : <50mA Alarm terms : Sound (vibration) and light alarm simultaneously Waterproof : IP31 Alarm Sound : ≥75dB(A) Op. Frequency : 40KHz WITHOUT BATTERY	ZKBioCV-IVS-VP (Video Patrol) ZKBIOCV ACCESS SOFTWARE Enable Video Patrol	ZKBS-IVS-P160 (BASIC) ZKBIOCV ACCESS SOFTWARE Max Supported Channels:160	ZKBS-IVS-P256 (ECONOMICS) ZKBIOCV ACCESS SOFTWARE Max Supported Channels: 256	ZKBS-IVS-AO-S1 (BASIC 65-256 CH) ZKBIOCV ACCESS SOFTWARE Add-on package 1: single channels add-on	ZKBS-IVS-AO-S2 (BASIC 65-256 CH) ZKBIOCV ACCESS SOFTWARE Add-on package 2: 8 channels add-on			
HBL400 RESIDENTIAL LOCKS	TL800 RESIDENTIAL LOCKS	TL700W RESIDENTIAL LOCKS	ML300 RESIDENTIAL LOCKS	LH5000 RESIDENTIAL LOCKS	LH4000 RESIDENTIAL LOCKS	ZKBioCV-AC-P50 (SME 50 doors) ZKBIOCV SECURITY SOFTWARE • 50 doors • 30,000 personnel ,2000 dept. • Unlimited login accounts	ZKBioCV-AC-P75 (ENTERPRISE 75 doors) ZKBIOCV SECURITY SOFTWARE • 75 doors • 30,000 personnel ,2000 dept. • Unlimited login accounts	ZKBioCV-AC-P100 (MNC 100 doors) ZKBIOCV SECURITY SOFTWARE • 100 doors • 30,000 personnel ,2000 dept. • Unlimited login accounts	ZKBioCV-AC-ADDON-S1 (Add-on Door Pkg) ZKBIOCV SECURITY SOFTWARE Range: 26- 100 Door	ZKBioCV-AC-P5 (Add-on Door Pkg) ZKBIOCV SECURITY SOFTWARE Add-on Door Quantity: 5
ML100 RESIDENTIAL LOCKS	GL300 SMART LOCKS	ZL500 HOTEL LOCKS	LH-7800 HOTEL LOCKS	LH-7500 HOTEL LOCKS	LH-6800 HOTEL LOCKS	ZKBioCV-AC-PRJ (ENTERPRISE Project) ZKBIOCV SECURITY SOFTWARE Supported doors>100 Supported Personnel>30,000	ZKBioCV-TA-P5 (BASIC 5 Points) ZKBIOCV SECURITY SOFTWARE • 30,000 personnel, 2000 dept. • Unlimited login accounts • Unlimited shifts	ZKBioCV-TA-P10 (BASIC 10 Points) ZKBIOCV SECURITY SOFTWARE • 30,000 personnel, 2000 dept. • Unlimited login accounts • Unlimited shifts	ZKBioCV-TA-P25 (ECONOMIC 25 Points) ZKBIOCV SECURITY SOFTWARE • 30,000 personnel, 2000 dept. • Unlimited login accounts • Unlimited shifts	ZKBioCV-TA-P50 (SME 50 Points) ZKBIOCV SECURITY SOFTWARE • 30,000 personnel, 2000 dept. • Unlimited login accounts • Unlimited shifts
D147-H NON-CONTACT SMART USB HOTEL IC CARD ENCODER	SLG410 ZIGBEE GATEWAY FOR WIRELESS HOTEL LOCK	SLG200 WIRELESS BLUETOOTH GATEWAY	ZK-IWB65BM • UHD 4K(3840*2160P) • Slim bezel design, • Anti-glare Glass • 6W*2 Speaker, • 16Wx1 Rear subwoofer • Embedded Microphone • Embedded Camera • Excellent touch performance • Support wireless screen casting • Built-in Android 11.0 • 8G RAM+64G ROM	INTERACTIVE WHITEBOARD 65" / 75" / 86" 		ZKBioCV-ELE-ONLINE-PR (Elevator Control Module Project) ZKBIOCV SECURITY SOFTWARE Support Personnel > 30,000 Supported Pannel (EC10)>10 Please Contact philtq, Request for Quote	Hotel Module (Per Lock) ZKBIOCV SECURITY SOFTWARE Support Personnel > 30,000 Supported Pannel (EC10)>10	ZKBioCV-Ent-P1 (Per Panel) ZKBIOCV SECURITY SOFTWARE • 30,000 personnel,2,000 dept. • Support Anti-passback,Linkage; • Support PG10 ic controller and Gate Barrier management'	ZKBioCV-Ent-P2 (Per Panel) ZKBIOCV SECURITY SOFTWARE • 30,000 personnel,2,000 dept. • Support Anti-passback,Linkage; • Support PG10 ic controller and Gate Barrier management'	ZKBioCV-Ent-PRJ (Per Panel) ZKBIOCV SECURITY SOFTWARE Supported PGIC10 Controller>20 Please Contact philtq , Request for Quote
20th Flr. Global Business Tower #144 Mayor Ignacio Santos Diaz cor. N. Domingo St Cubao, Q.C. For inquiries please call (+632) 8288 9029 / (+632) 8855 5037 / (+632) 3411 4977 email: marketing@philtq.com.ph website: www.philtq.com.ph										